



MOTOR OIL TREATMENT + MoS2

BENEFITS

- ✓ Significantly reduces friction and wear by forming a high load-bearing lubricating MoS2 film on all friction and sliding surfaces inside the engine
- ✓ Reduces fuel and oil consumption and lowers toxic emissions
- ✓ Improves viscosity of the oil and restores engine power
- ✓ Sub-micron sized MoS2 particles guarantee lubrication during cold starts and in case of emergencies
- ✓ Selected additives guarantee lower friction, effective long term protection of your engine and optimal performance.

USAGE

For all gasoline, diesel and LPG engines with or without turbochargers. Can be mixed with all commercially available engine oils. Does not clog filters and is not harmful for catalytic converters.

DIRECTION

Shake well before use. Add contents of one bottle to the warm motor oil, preferably shortly after oil change. Make sure the oil contents do not exceed the maximum oil level in your engine.

DOSAGE

One bottle treats 3 to 5 litres of motor oil. Use one bottle just after every oil change.

OIL

Packaging details

Art. No.:	68120
Content:	125 ml
Packaging:	24x125 ml
Pallet:	99 cartons
Languages:	EN, DE, FR, ES

Technical specifications

Density g/cm ³ :	0,89
Flash Point:	> 175°C
Colour:	Blackish
Odour :	Characteristic



VISIT US:

