



CERAMIC ENGINE PROTECTOR

BENEFITS

- ✓ Significantly reduces friction and wear
- ✓ Reduces fuel and oil consumption
- ✓ Restores engine power
- ✓ Provides long term protection of your engine
- ✓ Improves load carrying capacity of the lube film
- ✓ Reduces emission of hazardous exhaust gases

USAGE

For all gasoline, diesel and LPG engines with or without turbochargers. Can be mixed with all commercially available engine oils. Does not clog filters and is not harmful for catalytic converters. Not suitable for motorcycles using a wet clutch.

DIRECTION

Shake well before use. Add contents of one bottle to the warm motor oil, preferably shortly after oil change. Drive approximately 15 minutes to obtain optimum result. Make sure the oil contents do not exceed the maximum oil level in your engine.

DOSAGE

One bottle treats 4 to 6 litres of motor oil. Due to its outstanding bonding to metal, this advanced product retains its properties and effectiveness even after oil change. Recommended use: every 50.000 km.



OIL

Packaging details

| | |
|------------|----------------|
| Art. No.: | 68130 |
| Content: | 450 ml |
| Packaging: | 12x450 ml |
| Pallet: | 70 cartons |
| Languages: | EN, DE, FR, ES |

Technical specifications

| | |
|-----------------------------|---------------|
| Density g/cm ³ : | 0,90 |
| Flash Point: | > 200°C |
| Viscosity @ 20°C: | ~ 720 mPa.s |
| Colour: | Cream / White |

VISIT US:

