



BRAKE FLUID DOT 4

PRODUCT DESCRIPTION

ARDINA Brake Fluid DOT 4 is a high performance brake and clutch fluid with a minimum dry boiling point of 250 °C. Greatly exceeds SAE J1703 / J1704, FMVSS Nr.116 DOT 3 / DOT 4 and ISO 4925 specifications. Its high boiling point increases durability and safety. Provides excellent corrosion protection and rubber seal compatibility.

USAGE

Suitable for all hydraulic brake and clutch systems requiring synthetic fluid of DOT 4 specifications.

DIRECTION

Follow vehicle manufacturer's instructions when adding or replacing brake fluid. Miscible with all other brake fluids of DOT 4 specification. Must not be mixed with silicone type or silicone ester type of brake fluids. Store brake fluid clean and dry. Avoid contamination with fluids of any other kind and do not refill the container. Store brake fluid in the original container only. Keep the container tightly closed to prevent the absorption of moisture. Do not spill on car lacquer.

DOSAGE

Follow the service interval recommended by the car manufacturer. If no recommendation is given, it is advised to replace brake fluid at least every two years, preferably every year, every

SPECIALITY

Specifications & typical values

Properties	Unit	DOT 4 Specification	Typical Value
Appearance	-	-	Clear Liquid
Colour	-	-	Light Amber
Density at 20 °C	g/ml	-	1.06
Water content %	%(m/m)	-	max 0.20
Equilibrium Reflux			
Boiling Point (ERBP)	°C	≥ 230	260
Wet Equilibrium Reflux			
Boiling Point (WERBP)	°C	≥ 155	160
Kinematic viscosity			
at - 40 °C	mm ² /s	≤ 1800	1400
at 100 °C	mm ² /s	≥ 1.5	2.2



VISIT US:

