



ENGINE FLUSH

BENEFITS

- ✓ Internally cleans and flushes the engine with highly effective cleaning agents
- ✓ Eliminates gums, varnish and sludge
- ✓ Easily removes contaminants like carbon deposits, soot and liquids (water and fuel rests) from the engine
- ✓ Reduces fuel consumption and exhaust emissions by restoring engine condition and enabling the fresh oil to perform optimally
- ✓ Contains no harmful solvents

USAGE

For all gasoline, diesel and LPG engines with or without turboc hargers. Compatible with all mineral, semi synthetic or full synthetic motor oils.

DIRECTION

1. Before changing oil, pour the contents of one bottle in the crank case of the warm engine.
2. Let the engine run for 15 minutes, alternatively at low and high rpm.
3. Drain the oil from the crank case.
4. Replace oil filter.
5. Refill crank case with recommended fresh motor oil.

DOSAGE

One bottle treats a crankcase of 3 to 6 litres.

OIL

Packaging details

Art. No.:	68213
Content:	250 ml
Packaging:	24x250 ml
Pallet:	50 cartons
Languages:	EN, DE, FR, ES

Technical specifications

Density g/cm ³ :	0,87
Flash Point:	> 200°C
Coulour:	Clear / Amber
Odour :	Characteristic



VISIT US:

