MOTOR OIL SAE 5W30 ECO



PRODUCT DESCRIPTION

ARDINA Motor Oil SAE 5W30 ECO is a modern synthetic universal engine oil. Based on specially selected synthetic base oils with a high viscosity index. Combined with the specially selected high tech additives this motor oil is suitable for use in petrol and diesel engines with or without a turbo-charger in passenger cars and delivery vans.

PERFORMANCE LEVEL

- ACEA A3/B4
- API SH/CF
- BMW Longlife-01
- ✓ MB 229.3/226.5
- Renault RN0700
- ✓ VW 502.00/505.00

TECHNICAL SPECIFICATIONS

Density kg/L @ 15°C	0,857
Viscosity @-35°C mPa.s	5900
Viscosity @ 40°C mm2/s	72,80
Viscosity @ 100°C mm2/s	12,15
Viscosity Index	162
Flash Point COC	228°C
Pour Point	-39°C
Total Base Number	10,3 mgKOH/g
Ash, Sulphated	1,33%

PACKAGING DETAILS

rt. No.	68522
	65732

Content	1L/4L/5L/200L
Pallet	N/A



sales@ardinacarcare.com

The content of this sheet is correct to the best of our knowledge. We do not accept responsibility for damage as a consequence of incompleteness or negligence and inaccuracies in this in- formation sheet. Recommendations or suggestions made in this sheet are made without guarantee of respresentations as to results. All terms of sale of the supplier are applied here.